

# EXAMINER'S AMENDMENT

Application No. 09/510,652  
Reply to Office Action of February 28, 2006

84. (Previously Presented) The receiving apparatus for receiving signals in the digital telecommunication system according to claim 77, wherein an output signal of said detecting means is supplied to peak threshold detection means and gap detection means, wherein said correlation peak detected by said detecting means is confirmed or not based on detection results of said peak threshold detection means and said gap detection means.

85. (Previously Presented) The receiving apparatus for receiving signals in the digital telecommunication system according to claim 84, wherein said peak threshold detection means detects if the output signal of the detecting means exceeds a predetermined correlation peak threshold, and the gap detection means detects if the output signal of said detecting means has been below a predetermined gap threshold before said detected correlation peak.

86. (Previously Presented) The receiving apparatus for receiving signals in the digital telecommunication system according to claim 85, further comprising delay means for delaying the output signal of said detecting means before the output signal is supplied to said ~~detection~~  
gap ~~detecting~~ means.

87. (Previously Presented) The receiving apparatus for receiving signals in the digital telecommunication system according to claim 85, wherein said gap detection means detects if the output signal of said detecting means has been below said predetermined gap threshold during a predetermined gap time.

88. (Previously Presented) A method for synchronizing a receiving apparatus in a digital telecommunication system, comprising:

receiving a reference symbol including a plurality of successive repetition patterns, wherein each repetition pattern includes a number of complex samples, the number of complex samples being the same in each repetition pattern, and wherein one of the plurality of repetition patterns is phase-shifted in relation to the other repetition patterns;

cross-correlating said received reference symbol to generate an output signal;

detecting a phase of each of the plurality of repetition patterns in said reference symbol and detecting a correlation peak that indicates a position of the phase-shifted repetition pattern; and

synchronizing the receiving apparatus in the digital telecommunication system using said detected phases of each of said plurality of repetition patterns and said detected correlation peak.

89. (Previously Presented) The method according to claim 88, wherein said phase-shifted repetition pattern is phase-shifted by  $180^\circ$  in relation to the other repetition patterns.

90. (Previously Presented) The method according to claim 88, wherein, in said ~~cross-correlating~~ <sup>cross-correlating</sup> step, a correlation window is used that has a correlation window length corresponding to a length of one repetition pattern.

91. (Previously Presented) The method according to claim 90, wherein said detecting step comprises:

delaying the output signal generated in said correlation step by one repetition pattern length, and subtracting the delayed output signal from the output signal generated in said correlation step to generate a detection output signal.

92. (Previously Presented) The method according to claim 91, further comprising:  
smoothing the detection output signal.

93. (Previously Presented) The method according to claim 88, wherein, in said  
<sup>cross-correlating</sup>  
^ ~~correlation~~ step, a correlation window is used that has a correlation window length  
corresponding to a length of two repetition patterns.

94. (Previously Presented) The method according to claim 93, wherein said  
<sup>cross-correlating</sup>  
^ ~~correlation~~ step uses a positive and a negative conjugation of an expected repetition pattern  
for detecting a position of said correlation peak.

95. (Previously Presented) The method according to claim 88, wherein steps of peak  
threshold detection and gap detection are performed after said detecting step, and wherein  
said correlation peak detected in said detecting step is confirmed or not based on the  
detection results of said peak threshold detection step and said gap detection step.

96. (Currently Amended) The method according to claim 95, wherein said peak  
threshold detection step detects if <sup>a correlation</sup> ~~the detection~~ an output signal generated in said step of  
detecting the correlation peak exceeds a predetermined correlation peak threshold, and said  
gap detection step detects if the <sup>correlation</sup> ~~detection~~ output signal has been below a predetermined gap  
threshold before said detected correlation peak.

97. (Currently Amended) The method according to claim 96, further comprising:  
<sup>correlation</sup>  
delaying the ~~detection~~ output signal before said gap detection step is performed.

98. (Currently Amended) The method according to claim 96, wherein the step of gap detection comprises:

detecting if the <sup>correlation</sup> ~~detection~~ output signal has been below said predetermined gap threshold during a predetermined gap time.